

AD-A110 935

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OH F/G 13/8  
A STAND FOR THE GRINDING AND POLISHING OF ASPHERICAL SURFACES, (U)  
JAN 82 N P ZAKAZNOV, V V GORELIK, L V IVANOV  
FTD-ID(RS)T-1530-81

UNCLASSIFIED

NL

for 1  
AD  
A110935



END

DATE

FILED


NTIC

2

FTD-ID(RS)T-1530-81

AD A110935


# FOREIGN TECHNOLOGY DIVISION



A STAND FOR THE GRINDING AND POLISHING  
OF ASPHERICAL SURFACES

by

N.P. Zakaznov, V.V. Gorelik, L.V. Ivanov



Approved for public release;  
distribution unlimited.

WTC FILE COPY

82 02 16 065

# EDITED TRANSLATION

FTD-ID(RS)T-1530-81

29 January 1982

MICROFICHE NR: FTD-82-C-000108

A STAND FOR THE GRINDING AND POLISHING OF ASPHERICAL SURFACES

By: N.P. Zakaznov, V.V. Gorelik, L.V. Ivanov

English pages: 3

Source: USSR Patent Nr. 218688, 22 Dec 1969, pp. 1-2

Country of origin: USSR

Translated by: Joseph E. Pearson

Requester: USAMICOM

Approved for public release; distribution unlimited.

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By _____	
Dist _____	
Avail _____	
Dist _____	
A	

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION  
FOREIGN TECHNOLOGY DIVISION  
WP.AFB, OHIO.

FTD-ID(RS)T-1530-81

Date 29 Jan 1982

# U. S. BOARD ON GEOGRAPHIC NAMES TRANSLITERATION SYSTEM

Block	Italic	Transliteration	Block	Italic	Transliteration
А а	<i>А а</i>	A, a	Р р	<i>Р р</i>	R, r
Б б	<i>Б б</i>	B, b	С с	<i>С с</i>	C, s
В в	<i>В в</i>	V, v	Т т	<i>Т т</i>	T, t
Г г	<i>Г г</i>	G, g	У у	<i>У у</i>	U, u
Д д	<i>Д д</i>	D, d	Ф ф	<i>Ф ф</i>	F, f
Е е	<i>Е е</i>	Ye, ye; E, e*	Х х	<i>Х х</i>	Kh, kh
Ж ж	<i>Ж ж</i>	Zh, zh	Ц ц	<i>Ц ц</i>	Ts, ts
З з	<i>З з</i>	Z, z	Ч ч	<i>Ч ч</i>	Ch, ch
И и	<i>И и</i>	I, i	Ш ш	<i>Ш ш</i>	Sh, sh
Я я	<i>Я я</i>	Y, y	Щ щ	<i>Щ щ</i>	Shch, shch
К к	<i>К к</i>	K, k	Ъ ъ		"
Л л	<i>Л л</i>	L, l	Ы ы	<i>Ы ы</i>	Y, y
М м	<i>М м</i>	M, m	Ь ь		'
Н н	<i>Н н</i>	N, n	Э э	<i>Э э</i>	E, e
О о	<i>О о</i>	O, o	Ю ю	<i>Ю ю</i>	Yu, yu
П п	<i>П п</i>	P, p	Я я	<i>Я я</i>	Ya, ya

\*ye initially, after vowels, and after s, z, e elsewhere.  
When written as ѣ in Russian, transliterate as yě or ē.

## RUSSIAN AND ENGLISH TRIGONOMETRIC FUNCTIONS

Russian	English	Russian	English	Russian	English
sin	sin	sh	sinh	arc sh	sinh <sup>-1</sup>
cos	cos	ch	cosh	arc ch	cosh <sup>-1</sup>
tg	tan	th	tanh	arc th	tanh <sup>-1</sup>
ctg	cot	cth	coth	arc cth	coth <sup>-1</sup>
sec	sec	sch	sech	arc sch	sech <sup>-1</sup>
cosec	csc	csch	csch	arc csch	csch <sup>-1</sup>

## Russian English

rot curl  
lg log

A Stand for the Grinding and Polishing of Aspherical  
Surfaces

Originators of the invention: N. P. Zakaznov, V. V. Gorelik,  
L. V. Ivanov.

Applicants: Moscow Institute of Geodesy, Aerial Photography  
and Cartography Engineers and the Krasnogorsk  
Mechanical Plant.

Stands are known for the grinding and polishing of optical components, which (the stands) contain a tool with variable curvature, connected by means of a crank mechanism with an articulation.

The proposed stand is distinguished from the known stands by the fact, that it is equipped with a copying mechanism, and the crank mechanism is connected with the latter by means of an articulation, which makes it possible to increase the processing accuracy and to obtain aspherical surfaces of different radii.


The stand being described is schematically depicted in vertical cross section in the drawing.

For the shape forming of aspherical surfaces tool 1 is employed, which is turned with the aid of articulation 2, , placed in housing 3 and which imparts motion to crank mechanism 4, connected by housing 3 with copying device 5.

A surface of the required curvature is obtained, in this case, by maintaining the pre-calculated depth of the mutual immersion of the tool and the work-piece, monitored during the processing. The turning of the component (under the effect of the spring and the copying device) by a specific angle, the magnitude of which depends on the shape of the copying device, corresponds to any, as little as necessary, movement of a component with a convex surface downward.

The Patent Claims:

The stand for the grinding and the polishing of aspherical surfaces of optical components, which contains a tool with variable curvature of the working surface, connected by means of a crank mechanism with an articulation, which is distinguished by the fact, that, for the purpose of obtaining surfaces of different radii of curvature and increasing the processing accuracy, the stand is equipped with a copying device, and the crank mechanism is connected with the latter by means of an articulation accommodated in the housing.



FILMED  
8